



公司旗下实体 MEMBERS:

宏博音响（中国）有限公司

HONBO AUDIO CHINA LIMITED(HK)

Web:www.asdsound.com E-mail:sales@asdsound.com

Tel:+852 30501883 Fax:+852 30501886

深圳市爱尚达电子有限公司

SHENZHEN ACESOUND ELECTRONICS CO.,LTD

Web:www.acemic.com E-mail:acemic03@163.com

Tel:+86 755 28905200 Fax:+86 755 89716380

恩平市宏博音响科技有限公司

ENPINGHONGBO AUDIO TECHNOLOGY CO.,LTD.

Web:www.acemic.com E-mail:acemic03@163.com

Tel:+86 750 7122171 Fax:+86 750 7122510

ACEMIC AND ACESOUND LOGO ARE TRADEMARKS OF HONBO AUDIO
SPECIFICATIONS AND PICTURES SUBJECT TO CHANGE WITHOUT NOTICE

© 2023 HONBO AUDIO.ALL RIGHTS RESERVED

全国免费服务热线 4008-596-520



WEBSITE



FACEBOOK



PROFESSIONAL MICROPHONE

专业音视频麦克风

DSLR/CAMERA WIRELESS MICROPHONE 单反/摄像机无线音频麦克风

SMARTPHONE WIRELESS MICROPHONE 手机专用无线采访麦克风

DSLR/CAMERA SHOTGUN MICROPHONE 专业枪式采访麦克风

DSLR/SMARTPHONE LAVALIER MICROPHONE 手机/相机领夹麦克风



WWW.ACEMIC.COM

深圳市爱尚达电子有限公司

SHENZHEN ACESOUND ELECTRONICS CO.,LTD

HONBO AUDIO CHINA LIMITED

公司简介 ABOUT US

深圳市爱尚达电子有限公司是一家从事专业音频产品研发、生产、销售、服务于一体的高科技民营企业。公司自2007年创立以来，一直专注于无线音频产品的研发及生产。产品广泛应用于专业舞台、摄影器材、乐器、会议等各种音视频领域。

公司拥有先进的生产设备、高精度的检测仪器、高效的研发及生产团队、成熟的销售网络和完善的售后服务。我们坚信高质稳定的质量和热情完善的服务是企业的生存之本，因此我们一直秉承客户至上的原则，成功开发出多款迎合市场需求的产品并严格把控质量，从原材料的投入到成品出厂，各个环节均有质量检测跟踪，努力做到精益求精，创造零缺陷。公司产品在设计原理、制造工艺、技术性能上都已经达到国际先进水平；凭借着优良的品质及优质的服务，深得广大客户的赞誉和信赖！

公司恪守“技术创新、科学管理、持续发展”的经营理念；树立“以人为本”为企业核心价值体系；标榜“制造世界一流的麦克风产品，打造世界知名的麦克风品牌”为企业愿景。热情欢迎广大客户咨询洽谈，精诚合作，共赢未来。

HONBO AUDIO is a High-tech factory specialized in the development, production and sales of professional audio products. Since 2007 the company has been engaged in developing and producing wireless audio products. The products are widely used in a variety of vocal activity field like stages, cameras, musical instruments, conference etc.

Our company has advanced production equipment, high-precision testing equipment, efficient engineering and production team, mature sales network and perfect after-sales service. We firmly believe that the high quality and good service is the survival of the enterprise, so we have been adhering to the principle of Customer First, to develop a variety of products to meet market needs and strictly control the quality from raw material purchasing to final packing and inspecting, strive to achieve excellence and create zero defect. The products in the design principles, manufacturing processes, technical performance have reached the international advanced level, by virtue of excellent quality and best service, our products won the praise and trust from our customers!

HONBO AUDIO adhere to the "technological innovation, scientific management, sustainable development" business philosophy; establish a "people-oriented" as our sense of worth; take "create world-class microphone products, become the world's leading microphone brand" as our hope. We sincerely welcome worldwide clients to consult the cooperation and create mutually beneficial relation in the future.

PRODUCT CATALOGUE 产品目录

DSLR/CAMERA WIRELESS MICROPHONE SYSTEM单反/摄影机无线采访麦克风系统	01-02
2.4G DSLR/SMARTPHONE WIRELESS LAVALIER MICROPHONE2.4G 手机/相机无线直播领夹麦克风	03
DSLR/CAMERA WIRELESS MICROPHONE SYSTEM单反/摄影机无线采访麦克风系统	04-05
DSLR/SMARTPHONE SHOTGUN MICROPHONES相机/手机专用机顶麦克风	06
SMARTPHONE LAVALIER MICROPHONES手机专用领夹麦克风	07
DSLR/SMARTPHONE LAVALIER MICROPHONES相机/手机专用麦克风	08
SMARTPHONE LAVALIER MICROPHONES手机专用领夹麦克风	09
COMPUTER/LAPTOP USB MICROPHONESUSB电脑专用麦克风	10
SHOTGUN MICROPHONES枪式采访麦克风	11-12





DV-500



DV-500H



DV-500T

DSLR/CAMERA/SMARTPHONE WIRELESS MICROPHONE SYSTEM

UHF铝合金一拖一无线麦克风系统（锂电池）

产品特点 FEATURES:

- UHF 600-937频段（常规频率660-690MHz）。
- 铝合金腰包机壳，坚固耐用。
- 支持耳机监听和线路输出。
- 预设100组精选频道。
- 红外线自动对频。
- SMA可拆卸式天线。
- 内置3.7V锂电池供电。
- OLED 液晶显示屏显示频道，频率数值，电池电量等。
- 空旷使用距离50米。
- 摄像机/DV/单反/手机录音采访专用。
- UHF 600-937MHz frequency range(Region dependant)
- Durable aluminum alloy body-pack
- Preset 100 selectable channels
- Seperate earphone monitor output and line output
- IR sync downloading the frequency from receiver
- SMA detachable antennas
- Built-in 3.7V lithium battery
- OLED display shows status of channel and battery life
- Up to 50m line-of-sight operating range
- Special designed for Camera/DV/DSLR/cellphone recording applications

技术参数 SPECIFICATION:

综合性能 Comprehensive Performance:

- 频率范围 Frequency Range: UHF600-937MHz
- 调制方式 Modulation Mode: FM
- 动态范围 Dynamic Range: >100dB
- 频率响应 Frequency Response: 60Hz-17KHz $\pm$ 3dB
- 失真度 Total Harmonic Distortion: <0.5% at 1KHz
- 信噪比 Signal/Noise Ratio: $\geq$ 105dB

接收机 Receiver:

- 频率范围 Frequency Range: 600-937MHz
- 接收灵敏度 Receive Sensitivity: $\sim$ 110dBm(sinad>30dB)
- 信噪比 Signal/Noise Ratio: >105dB
- 供电电压 Battery Voltage: 3.7V锂电池 Lithium battery

发射器 Transmitter:

- 频率范围 Frequency Range: 600-937MHz
- 射频功率 RF Power: 10mW
- 手咪供电电压 Handmic Battery Voltage: 3V (2X1.5V AA Battery)
- 腰包供电电压 Bodypack Battery Voltage: 3.7V锂电池 Lithium battery
- 手雷供电电压 Plug-on TX Battery Voltage: 3.7V锂电池 Lithium battery
- 持续使用时间 Power Consumption: 6 小时 hours



DV-500DUAL

DUAL CHANNEL DSLR/CAMERA/SMARTPHONE WIRELESS MICROPHONE SYSTEM

UHF铝合金一拖二无线麦克风系统（锂电池）

产品特点 FEATURES:

- UHF 600-937频段（常规频率660-690MHz）。
- 铝合金腰包机壳，坚固耐用。
- 支持耳机监听和线路输出。
- 预设100组精选频道。
- 红外线自动对频。
- SMA可拆卸式天线。
- 内置3.7V锂电池供电。
- OLED 液晶显示屏显示频道，频率数值，电池电量等。
- 空旷使用距离50米。
- 摄像机/DV/单反/手机录音采访专用。

- UHF 600-937MHz frequency range(Region dependant)
- Durable aluminum alloy body-pack
- Preset 100 selectable channels
- Seperate earphone monitor output and line output
- IR sync downloading the frequency from receiver
- SMA detachable antennas
- Built-in 3.7V lithium battery
- OLED display shows status of channel and battery life
- Up to 50m line-of-sight operating range
- Special designed for Camera/DV/DSLR/cellphone recording applications

技术参数 SPECIFICATION:

腰包接收机 Body-pack Receiver:

- 频率范围 Frequency Range: 660-690MHz
- 频率响应 Frequency Response: 60Hz-17KHz $\pm$ 3dB
- 信噪比 S/N Ratio: $\geq$ 105dB($\sim$ 60dBm)
- 总谐波失真 T.H.D: <0.5% at 1KHz
- 动态范围 Dynamic Range: >100dB
- 接收灵敏度 Receive Sensitivity: $\sim$ 11dBm (sinad $\geq$ 30dB)
- 输出方式 Output: 3.5mm line out and earphone out
- 对频方式 Interface: 红外对频 Infrared
- 电源 Power Supply: 锂电池 Lithium battery
- 供电电压 Operating Voltage: 3.7V
- 持续使用时间 Operating time: 6h
- 材质 Material: 铝合金
- 尺寸 Dimensions(L*W*H) : 102*64*43mm

腰包发射器 Body-pack Transmitter:

- 频率范围 Frequency Range: 660-690MHz
- 频率偏移 Frequency Deviation : $\pm$ 48KHz
- 输入 Input : 3.5mm input and 3pin mini-XLR input
- RF输出 RF Output Power: 10mW
- 控制 Controls : Power ON/OFF, Volume, SET frequency
- 对频方式 Interface: 红外对频 Infrared
- 电源 Power Supply: 锂电池 Lithium battery
- 供电电压 Operating Voltage: 3.7V
- 持续使用时间 Operating time: 6h
- 材质 Material: 铝合金
- 尺寸 Dimensions(L*W*H) : 102*64*24mm

VLOG100

2.4G DSLR/SMARTPHONE WIRELESS LAVALIER MICROPHONE

2.4G 手机/相机专用无线直播领夹麦克风系统

产品特点 FEATURES:

- 2.4G无线音频传输。
- V1(一拖一单通道) / V2(一拖二双通道) / V4(一拖一单通道)。
- 内置锂电池供电。
- 发射器支持内置咪芯拾音或外接领夹麦克风。
- 接收器可连接相机、手机、平板等设备录音、直播。
- 空旷有效使用距离15米。
- 单反相机/手机VLOG直播、采访、录播专用。
- 2.4GHz digital frequency
- V1(single channel) / V2(dual channels) / V4(single channel)
- Built-in microphone or use external tie-clip microphone
- Receiver can connect cameras, smartphones and Pads
- Up to 15m line-of-sight operating range
- Special designed for DSLR/mobile interview/vlogrecording

技术参数 SPECIFICATION:

- 工作频段 Working frequency band: ISM 2.4GHz(2405~2478MHz)
- 信道数 Channels: 内置20个信道数 Pre-set 20 adjustable channels
- 调制模式 Modulation mode: GFSK数字调制/解调 demodulation
- 频率响应 Frequency response: 50Hz ~ 16KHz
- 延时时间 Latency: <5ms
- 采样率 Sampling rate: 32KHz*24bit
- 信噪比 Signal to noise ratio: >90dB
- 动态范围 Dynamic range: >95dB
- 通讯距离 Operation distance: 15m(无障碍物) (open area)
- 电源 Power supply: 内置3.7V可充式锂电池 lithium battery
- 电池续航 Battery life: 5小时 hours
- 拾音模式 Pickup pattern: 全向 Omni-directional
- 天线 Antenna: PIFA天线 antenna
- 工作温度 Working temperature: -10 ~ +55°C
- 材料 Material: ABS
- 产品尺寸 Product size: V1/ V2: 77x12.8x35mm
V4: 35 x 17.2 x 62.8 mm
- 产品净重 Product net weight: 12g



V1



V2



V4



DV-100



DV-100H



DV-100T

DSLR/CAMERA/SMARTPHONE WIRELESS MICROPHONE SYSTEM

UHF一拖一无线麦克风系统

产品特点 FEATURES:

- 超高频UHF 600~937频段。
- 真分集保证最大距离接收不断频。
- 采用PLL锁相环频率稳定系统。
- 预设100 (10*10) 组精选调频。
- 红外线自动对频。
- LCD显示工作频率, 信号强度等工作状态。
- 空旷使用距离80米。
- 摄像机/单反相机/手机采访录播专用。
- UHF 600~937MHz frequency range
- True diversity for maximum range and dropout protection
- PLL Synthesized circuit, pre-set 100 selectable frequencies
- Pre-set 100 selectable frequencies
- IR sync downloading the frequency
- LCD display shows status of frequency, AF and RF signal etc
- Up to 80m line-of-sight operating range
- Special designed for Camera/DSLR/Mobile interview recording

技术参数 SPECIFICATION:

综合性能 Comprehensive Performance:

- 频率范围 Frequency Range: UHF600~937MHz
- 调制方式 Modulation Mode: FM
- 动态范围 Dynamic Range: >100dB
- 频率响应 Frequency Response: 60Hz~17KHz ± 3dB
- 失真度 Total Harmonic Distortion: <0.5% at 1KHz
- 信噪比 Signal/Noise Ratio: ≥ 105dB

接收机 Receiver:

- 频率范围 Frequency Range: 600~937MHz
- 接收灵敏度 Receive Sensitivity: -110dBm(sinad>30dB)
- 信噪比 Signal/Noise Ratio: >105dB
- 供电电压 Battery Voltage: 3V (2X1.5V AA Battery)

发射器 Transmitter:

- 频率范围 Frequency Range: 600~937MHz
- 射频功率 RF Power: 10mW
- 手咪供电电压 Handmic Battery Voltage: 3V (2X1.5V AA Battery)
- 腰包供电电压 Bodypack Battery Voltage: 3V (2X1.5V AA Battery)
- 手雷供电电压 Plug-on TX Battery Voltage: 3.7V (锂电池 Lithium Battery)
- 持续使用时间 Power Consumption: 6 小时 hours



DV-20



DV-20H1



DV-20T

DSLR/CAMERA/SMARTPHONE WIRELESS MICROPHONE SYSTEM

UHF一拖一无线麦克风系统

产品特点 FEATURES:

- 超高频UHF 600-937频段。
- 数字音频传输技术。
- 数字ID码导频，彻底解决同频串音。
- 预设16组精选可调频率。
- 红外线自动对频。
- LED数码管显示工作频道。
- 空阔使用距离40米。
- 摄像机/单反相机/手机采访录播专用。
- UHF 600-937MHz frequency range
- Digital wireless audio transmission
- Digital ID code, completely solve the frequency interference
- Pre-set 16 selectable frequencies
- IR sync downloading the frequency
- LED display shows status of working channel
- Up to 40m line-of-sight operating range
- Special designed for Camera/DSLR/Mobile interview recording

技术参数 SPECIFICATION:

综合性能 Comprehensive Performance:

- 频率范围 Frequency Range: UHF600-937MHz
- 调制方式 Modulation Mode: pi/4 DQPSK
- 动态范围 Dynamic Range: >100dB
- 频率响应 Frequency Response: 80Hz-15KHz $\pm$ 3dB
- 失真度 Total Harmonic Distortion: <0.5% at 1KHz
- 信噪比 Signal/Noise Ratio: $\geq$ 95dB

接收机 Receiver:

- 频率范围 Frequency Range: 600-937MHz
- 接收灵敏度 Receive Sensitivity: $-94\text{dBm}(\text{sinad}>30\text{dB})$
- 信噪比 Signal/Noise Ratio: >95dB
- 供电电压 Battery Voltage: 3V (2X1.5V AA Battery)

发射器 Transmitter:

- 频率范围 Frequency Range: 600-937MHz
- 射频功率 RF Power: 10mW
- 手咪供电电压 Handmic Battery Voltage: 3V (2X1.5V AA Battery)
- 腰包供电电压 Bodypack Battery Voltage: 3V (2X1.5V AA Battery)
- 手雷供电电压 Plug-on TX Battery Voltage: 3.7V (锂电池 Lithium Battery)
- 持续使用时间 Power Consumption: 6 小时 hours



CAM50PLUS



CAM50



CAM20

DSLR/SMARTPHONE SHOTGUN MICROPHONES

相机/手机专用机顶麦克风

CAM50Plus

相机/手机专用麦克风 (带监听)
Portable DSLR/Mobile Microphone (Ear monitor)

- 咪芯类型 Capsule Type: 电容式 Condenser
- 指向性 Polar Pattern: 心型 Cardioid
- 频率响应 Frequency Response: 100Hz-20KHz
- 输出阻抗 Output Impedance: 2.2K Ω
- 最大声压级 Max SPL: 110dB (at 1kHz $\leq$ 1% T.H.D)
- 灵敏度 Sensitivity: $-38\text{dB } 1\text{V/Pa @ } 1\text{KHz}$
- 信噪比 Signal/Noise Ratio: 78dB
- 电源需求 Power Requirement: 3V by DSLR
- 尺寸 Dimension: L80* ϕ 26mm

CAM50

相机/手机专用麦克风
Portable DSLR/Mobile Microphone

- 咪芯类型 Capsule Type: 电容式 Condenser
- 指向性 Polar Pattern: 心型 Cardioid
- 频率响应 Frequency Response: 100Hz-20KHz
- 输出阻抗 Output Impedance: 2.2K Ω
- 最大声压级 Max SPL: 110dB (at 1kHz $\leq$ 1% T.H.D)
- 灵敏度 Sensitivity: $-38\text{dB } 1\text{V/Pa @ } 1\text{KHz}$
- 信噪比 Signal/Noise Ratio: 65dB
- 电源需求 Power Requirement: 3V by DSLR
- 尺寸 Dimension: L80* ϕ 21mm

CAM20

迷你版相机/手机专用麦克风
Mini DSLR/Mobile Microphone

- 咪芯类型 Capsule Type: 电容式 Condenser
- 指向性 Polar Pattern: 心型 Cardioid
- 频率响应 Frequency Response: 100Hz-20KHz
- 输出阻抗 Output Impedance: 680 Ω
- 最大声压级 Max SPL: 100dB (at 1kHz $\leq$ 1% T.H.D)
- 灵敏度 Sensitivity: $-47\text{dB } 1\text{V/Pa @ } 1\text{KHz}$
- 信噪比 Signal/Noise Ratio: 55dB
- 电源需求 Power Requirement: 3V by DSLR
- 尺寸 Dimension: L43* ϕ 14.5mm

SMARTPHONE
LAVALIER MICROPHONES

手机专用领夹麦克风



M1-A

M1-A
苹果手机专用有线领夹式麦克风
Lightning Lavalier Microphone For iPhone

- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 20Hz-16KHz
- 连接器 Connector: Lightning Plug
- 最大声压级 Max SPL: 58dB
- 灵敏度 Sensitivity: -34dB +/- 2dB (0dB=1V/Pa, 3V)
- 长度 Length: 1.5m
- 重量 Weight: 25g



M1-B

M1-B
安卓手机专用有线领夹式麦克风
Type-C Lavalier Microphone For Android Phone

- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 20Hz-16KHz
- 连接器 Connector: Type-C Plug
- 最大声压级 Max SPL: 58dB
- 灵敏度 Sensitivity: -34dB +/- 2dB (0dB=1V/Pa, 3V)
- 长度 Length: 1.5m
- 重量 Weight: 25g



M1-A1

M1-A1
苹果手机专用有线领夹式麦克风 (带耳机孔)
Lavalier mic for Iphone (with earphone jack)

- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 20Hz-16KHz
- 连接器 Connector: Lightning Plug
- 最大声压级 Max SPL: 58dB
- 灵敏度 Sensitivity: -34dB +/- 2dB (0dB=1V/Pa, 3V)
- 长度 Length: 1.5m
- 重量 Weight: 25g



M1-B1

M1-B1
安卓手机专用有线领夹式麦克风 (带耳机孔)
Lavalier mic for Android smartphone (with earphone jack)

- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 20Hz-16KHz
- 连接器 Connector: Type-C Plug
- 最大声压级 Max SPL: 58dB
- 灵敏度 Sensitivity: -34dB +/- 2dB (0dB=1V/Pa, 3V)
- 长度 Length: 1.5m
- 重量 Weight: 25g

DSLR/SMARTPHONE
LAVALIER MICROPHONES

相机/手机专用麦克风



M11

M11
相机/手机专用有线领夹式麦克风 (单头)
Single Head Camera/Mobile Lavalier Microphone

- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 20Hz-20KHz
- 输出阻抗 Output Impedance: 680Ω
- 最大声压级 Max SPL: 100dB (T.H.D ≤ 1% at 1kHz)
- 灵敏度 Sensitivity: -35dB 1V/Pa @ 1KHz
- 信噪比 Signal/Noise Ratio: 68dB
- 线长 Cable Length: 6M



M12

M12
相机/手机专用有线领夹式麦克风 (双头)
Dual Head Camera/Mobile Lavalier Microphone

- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 20Hz-20KHz
- 输出阻抗 Output Impedance: 680Ω
- 最大声压级 Max SPL: 100dB (T.H.D ≤ 1% at 1kHz)
- 灵敏度 Sensitivity: -35dB 1V/Pa @ 1KHz
- 信噪比 Signal/Noise Ratio: 68dB
- 线长 Cable Length: 6M



EM1

EM1
多功能领夹式麦克风 (单头)
Single Head Multifunctional Lavalier Microphone

- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 20Hz-20KHz
- 输出阻抗 Output Impedance: 2200Ω
- 最大声压级 Max SPL: 100dB (T.H.D ≤ 1% at 1kHz)
- 灵敏度 Sensitivity: -30dB +/- 3dB/ 0dB=1V/Pa, 1kHz
- 信噪比 Signal/Noise Ratio: 74dB
- 线长 Cable Length: 6M



EM2

EM2
多功能领夹式麦克风 (双头)
Dual Head Multifunctional Lavalier Microphone

- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 20Hz-20KHz
- 输出阻抗 Output Impedance: 2200Ω
- 最大声压级 Max SPL: 100dB (T.H.D ≤ 1% at 1kHz)
- 灵敏度 Sensitivity: -30dB +/- 3dB/ 0dB=1V/Pa, 1kHz
- 信噪比 Signal/Noise Ratio: 74dB
- 线长 Cable Length: 6M*2

SMARTPHONE LAVALIER MICROPHONES

手机专用领夹麦克风



M1

M1
手机专用有线领夹式麦克风（单头）
Single Head Lavalier Microphone For Smartphone

- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 35Hz-18KHz
- 连接器 Connector: 3.5mm TRRS connector
- 最大声压级 Max SPL: 100dB
- 灵敏度 Sensitivity: $-30\text{dB} \pm 3\text{dB} / 0\text{dB} = 1\text{V/Pz}$, 1 KHz
- 信噪比 Signal/Noise Ratio: 65dB
- 线长 Cable Length: 1.5M



M2

M2
手机专用有线领夹式麦克风（双头）
Dual Head Lavalier Microphone For Smartphone


- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 35Hz-18KHz
- 连接器 Connector: 3.5mm TRRS connector
- 最大声压级 Max SPL: 100dB
- 灵敏度 Sensitivity: $-30\text{dB} \pm 3\text{dB} / 0\text{dB} = 1\text{V/Pz}$, 1 KHz
- 信噪比 Signal/Noise Ratio: 65dB
- 线长 Cable Length: 4M



M3

M3
手机专用有线领夹式麦克风（带耳机孔）
Single Head Lavalier Microphone For Smartphone (with earphone jack)

- 指向性 Polar Pattern: 全指向 Omni-Directional
- 频率响应 Frequency Response: 35Hz-18KHz
- 连接器 Connector: 3.5mm TRRS connector
- 最大声压级 Max SPL: 100dB
- 灵敏度 Sensitivity: $-30\text{dB} \pm 3\text{dB} / 0\text{dB} = 1\text{V/Pz}$, 1 KHz
- 信噪比 Signal/Noise Ratio: 65dB
- 线长 Cable Length: 1.5M



GM12

GM12
3.5mm鹅颈麦克风
3.5mm Microphone Input Gooseneck Line

- 指向性 Polar Pattern: 单指向 Uni-Directional
- 频率响应 Frequency Response: 240Hz-20KHz
- 输出阻抗 Output Impedance: 700Ω
- 最大声压级 Max SPL: 120dB (T.H.D $\leq 1\%$ at 1kHz)
- 灵敏度 Sensitivity: $-34\text{dB} 1\text{V/Pa}$ @ 1KHz
- 长度 Length: 16cm

COMPUTER/LAPTOP CONDENSER USB MICROPHONES

USB电脑专用麦克风



PCM90

PCM90
电脑专用USB电容麦克风
Computer Condenser USB Mic

- 指向性 Polar Pattern: 单指向 Uni-Directional
- 频率响应 Frequency Response: 100Hz-18KHz
- 输出阻抗 Output Impedance: 2200Ω
- 电源需求 Power Requirement: 10V
- 灵敏度 Sensitivity: $-42\text{dB} 1\text{V/Pa}$ @ 1KHz
- 信噪比 Signal/Noise Ratio: 58dB
- 线长 Cable Length: 1.8M



USB-700

USB-700
电脑专用USB电容麦克风
Computer Condenser USB Mic

- 指向性 Polar Pattern: 心型指向 Cardioid
- 信噪比 S/N: 60db
- 灵敏度 Sensitivity: $-42\text{dB} \leq S \leq -44\text{dB}$
- 采样率 Sampling rate: 192kHz/24bit
- 输出阻抗 Output impedance: 680Ω
- 负载阻抗 Load impedance: $\geq 1000\Omega$
- 消耗电流 Current consumption: 3mA



USB-800

USB-800
电脑专用USB电容麦克风
Computer Condenser USB Mic

- 指向性 Polar Pattern: 心型指向 Cardioid
- 灵敏度 Sensitivity: $-40\text{dB} \pm 2\text{dB}$ (0dB=1V/Pa, 3V)
- 输出阻抗 Output impedance: 680Ω
- 频率响应 Frequency Response: 20Hz-20KHz
- 最大声压级 Max SPL: 125dB
- 信噪比 S/N: 90dB
- 采样率 Sampling Rate: 192kHz/24bit
- 消耗电流 Current consumption: 3mA



USB-900

USB-900
双咪芯立体声电脑专用USB电容麦克风
Stereo Computer Condenser USB Mic

- 指向性 Polar Pattern: 双指向 Bidirectional
- 灵敏度 Sensitivity: $-40\text{dB} \pm 2\text{dB}$ (0dB=1V/Pa, 3V)
- 输出阻抗 Output impedance: 680Ω
- 频率响应 Frequency Response: 20Hz-20KHz
- 最大声压级 Max SPL: 125dB
- 信噪比 S/N: 90dB
- 采样率 Sampling Rate: 48kHz/16bit
- 电源需求 Power Requirement: USB 5V(DC)



DV-005



DV-006



DV-008

DSLR/CAMERA SHOTGUN MICROPHONES

专业枪式采访麦克风

DV-005

入门级枪式采访麦克风

Entry Level Shotgun Microphone

- 咪芯类型 Capsule Type: 电容式 Condenser
- 指向性 Polar Pattern: 单指向 Uni-Directional
- 频率响应 Frequency Response: 100Hz-16KHz
- 输出阻抗 Output Impedance: 1000Ω
- 灵敏度 Sensitivity: -38dB re 1V/Pa @ 1KHz
- 信噪比 Signal/Noise Ratio: 80dB
- 拾音距离 Pickup Distance: 5M
- 电源需求 Power Requirement: 1.5V AA Battery
- 长度 Length: 273mm

DV-006

入门级枪式采访麦克风

Entry Level Shotgun Microphone

- 咪芯类型 Capsule Type: 电容式 Condenser
- 指向性 Polar Pattern: 单指向 Uni-Directional
- 频率响应 Frequency Response: 100Hz-16KHz
- 输出阻抗 Output Impedance: 1000Ω
- 灵敏度 Sensitivity: -38dB 1V/Pa @ 1KHz
- 信噪比 Signal/Noise Ratio: 80dB
- 拾音距离 Pickup Distance: 5M
- 电源需求 Power Requirement: 1.5V AA Battery
- 长度 Length: 360mm

DV-008

入门级枪式采访麦克风(幻象供电)

Entry Level Shotgun Microphone

- 咪芯类型 Capsule Type: 电容式 Condenser
- 指向性 Polar Pattern: 单指向 Uni-Directional
- 频率响应 Frequency Response: 100Hz-20KHz
- 输出阻抗 Output Impedance: 1000Ω
- 灵敏度 Sensitivity: -38dB 1V/Pa @ 1KHz
- 信噪比 Signal/Noise Ratio: 80dB
- 拾音距离 Pickup Distance: 5M
- 电源需求 Power Requirement: 1.5V AA Battery/Phantom P48V
- 长度 Length: 360mm

DSLR/CAMERA SHOTGUN MICROPHONES

专业枪式采访麦克风

DV-011

广播级音质枪式采访麦克风

Broadcast Level Shotgun Microphone

- 咪芯类型 Capsule Type: 电容式 Condenser
- 指向性 Polar Pattern: 超心型 Hyper Cardioid
- 频率响应 Frequency Response: 100Hz-20KHz
- 输出阻抗 Output Impedance: 250Ω
- 灵敏度 Sensitivity: -32dB 1V/Pa @ 1KHz
- 信噪比 Signal/Noise Ratio: 90dB
- 拾音距离 Pickup Distance: 10M
- 电源需求 Power Requirement: 48V Phantom Power
- 长度 Length: 180mm

DV-015

广播级音质枪式采访麦克风

Broadcast Level Shotgun Microphone

- 咪芯类型 Capsule Type: 电容式 Condenser
- 指向性 Polar Pattern: 超心型 Hyper Cardioid
- 频率响应 Frequency Response: 100Hz-20KHz
- 输出阻抗 Output Impedance: 250Ω
- 灵敏度 Sensitivity: -32dB 1V/Pa @ 1KHz
- 信噪比 Signal/Noise Ratio: 90dB
- 拾音距离 Pickup Distance: 15M
- 电源需求 Power Requirement: 48V Phantom Power
- 长度 Length: 340mm

DV-018

超远距离枪式采访麦克风

Long Distance Shotgun Microphone

- 咪芯类型 Capsule Type: 电容式 Condenser
- 指向性 Polar Pattern: 超心型 Hyper Cardioid
- 频率响应 Frequency Response: 100Hz-20KHz
- 输出阻抗 Output Impedance: 250Ω
- 灵敏度 Sensitivity: -32dB 1V/Pa @ 1KHz
- 信噪比 Signal/Noise Ratio: 92dB
- 拾音距离 Pickup Distance: 25M
- 电源需求 Power Requirement: 48V Phantom Power
- 长度 Length: 545mm



DV-011



DV-015



DV-018